

# Package: ROlogit (via r-universe)

September 12, 2024

**Type** Package

**Title** Fit Rank-Ordered Logit (RO-Logit) Model

**Version** 0.1.2

**Author** Tan Chuen Seng, Ning Yilin

**Maintainer** Ning Yilin <ningyilinnyl@gmail.com>

**Description** Implements the rank-ordered logit (RO-logit) model for stratified analysis of continuous outcomes introduced by Tan et al. (2017) <[doi:10.1177/0962280217747309](https://doi.org/10.1177/0962280217747309)>. Model diagnostics based on the heuristic residuals and estimates in linear scales are available from the package, and outcomes with ties are supported.

**Depends** R (>= 3.1.0)

**Imports** survival (>= 2.41-3), evd (>= 2.3-2)

**License** LGPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Date/Publication** 2018-03-19 08:13:57 UTC

**Repository** <https://nyilin.r-universe.dev>

**RemoteUrl** <https://github.com/nyilin/rologit>

**RemoteRef** HEAD

**RemoteSha** b3411b91862b826a852418629d936f424bfbfb16

## Contents

hresid . . . . .	2
inpat_bg . . . . .	2
loglikhresid . . . . .	3
qqplot.EVT1 . . . . .	4

rologit . . . . .	4
rologit.coxph . . . . .	6
summary.rologit . . . . .	6

<b>Index</b>	<b>7</b>
--------------	----------

---

hresid	<i>Obtain the heuristic residuals.</i>
--------	--

---

### Description

Obtain the heuristic residuals.

### Usage

```
hresid(y, svar, design.mat, o, initial.res.par = c(0, 0), ...)
```

### Arguments

<code>y</code>	vector of numeric. The outcomes.
<code>svar</code>	vector of numeric. The strata variable.
<code>design.mat</code>	matrix. The design matrix including intercept term.
<code>o</code>	matrix. Contains the estimated coefficients of the RO-logit and their SEs.
<code>initial.res.par</code>	The initial values of the intercept and $\log(\text{scale})$ , to be passed to the <code>optim</code> function. The default values are set to $c(0, 0)$ , yet users are recommended to try a few initial values to make sure global optimum is reached.
<code>...</code>	Other parameters to be passed to the <code>optim</code> function. See <a href="#">optim</a> for details.

### Value

Returns a list containing the estimated intercept and  $\log(\text{scale})$ , the covariance matrix of these two parameters, convergence status from `optim`, and the heuristic residuals.

---

inpat_bg	<i>Inpatient blood glucose data for 2487 patients</i>
----------	---

---

### Description

A simulated dataset containing inpatient point-of-care blood glucose (BG) measurements from 2487 non-critical care adult patients above 40 years old. Data was simulated based on real data.

### Usage

```
inpat_bg
```

**Format**

A data frame with 2487 rows and 13 variables:

**bg\_mean** Mean BG readings within each episode, in mmol/L.

**bg\_sd** Standard deviation of BG readings within each episode.

**sex** Gender of patients.

**ward** Whether each patient is in the medical ward (ward = 0) or surgical ward (ward = 1).

**age\_group** Patient group defined based on the median age.

**los\_group** Patient group defined based on the median of duration of monitoring episode.

**bg\_freq\_group** Patient group defined based on the median of daily BG monitoring frequency.

**age** Patients' age.

**los** Patients' duration of monitoring episode.

**bg\_freq** Patients' daily BG monitoring frequency.

**References**

Tan CS, Støer NC, Chen Y, Andersson M, Ning Y, Wee HL, Khoo EY, Tai ES, Kao SL, Reilly M. A stratification approach using logit-based models for confounder adjustment in the study of continuous outcomes. *Statistical methods in medical research*. 2017 Jan 1:0962280217747309.

---

 loglikhresid

*The negative log likelihood function for obtaining heuristic residuals*


---

**Description**

Compute the negative log-likelihood for obtaining heuristic residuals.

**Usage**

```
loglikhresid(par, y, x, par1)
```

**Arguments**

par	vector of numeric. Contain the intercept, first entry, and coefficient of log(sigma), second entry.
y	vector of numeric. Centered outcomes within each stratum.
x	matrix. The design matrix including intercept term.
par1	vector of numeric. The estimated coefficients from RO-logit model.

`qqplot.EVT1`*Make Q-Q plot for residual diagnostics.*

---

**Description**

Make Q-Q plot for residual diagnostics.

**Usage**

```
qqplot.EVT1(hresid, scale)
```

**Arguments**

`hresid`            vector of numeric. The heuristic residuals.  
`scale`            numeric. The scale parameter.

**Examples**

```
## Not run:  
hresid <- evd::rgumbel(n = 100, loc = 0, scale = 3)  
qqplot.EVT1(hresid = hresid, scale = 3)  
  
## End(Not run)
```

---

`rologit`*Fit RO-logit model and obtain heuristic residuals*

---

**Description**

Fit RO-logit model and obtain heuristic residuals

**Usage**

```
rologit(  
  yvar,  
  evar,  
  cfdr = NULL,  
  emod = NULL,  
  svar,  
  dat,  
  method = "efron",  
  initial.res.par = c(0, 0),  
  plot = TRUE,  
  ...  
)
```

**Arguments**

<code>yvar</code>	string. Name of outcome variable.
<code>evar</code>	string (or vector of strings). Name of exposure(s).
<code>cfdr</code>	string (or vector of strings). Names of confounder(s). Default is NULL.
<code>emod</code>	string (or vector of strings). Name of effect modifier(s). Default is NULL.
<code>svar</code>	string. Name of stratum variable. Use NULL to fit model without stratification.
<code>dat</code>	<code>data.frame</code> . Contains all the variables needed for the analysis.
<code>method</code>	string. Use Efron ("efron") or Breslow ("breslow") method for handling ties in the outcome. The default is "efron". See <a href="#">coxph</a> for details.
<code>initial.res.par</code>	The initial values of the intercept and $\log(\text{scale})$ , to be passed to the <code>optim</code> function. The default values are set to $c(0, 0)$ , yet users are recommended to try a few initial values to make sure global optimum is reached.
<code>plot</code>	logic. To plot the Q-Q plot for the heuristic residuals. Default is TRUE.
<code>...</code>	Other parameters to be passed to the <code>optim</code> function for the second stage analysis.

**Value**

Returns a list containing `obj` (the RO-Logit model fitted using `coxph`), `hresid` (the vector of heuristic residuals), `logscale` (log of scale parameter of the heuristic residuals), and `coefficients` (a `data.frame` with estimated coefficients before and after scaling).

**References**

- Allison PD, Christakis NA. Logit-models for sets of ranked items. *Sociological Methodology* 1994, Vol 24. 1994;24:199-228.
- Beggs S, Cardell S, Hausman J. Assessing the Potential Demand for Electric Cars. *J Econometrics*. 1981;17:1-19.
- Tan CS, Støer NC, Chen Y, Andersson M, Ning Y, Wee HL, Khoo EY, Tai ES, Kao SL, Reilly M. A stratification approach using logit-based models for confounder adjustment in the study of continuous outcomes. *Statistical methods in medical research*. 2017 Jan 1:0962280217747309.
- Therneau TM, Grambsch PM. *Modeling Survival Data: Extending the Cox Model*: Springer New York; 2000.

**Examples**

```
# Fit an RO-logit model to determine whether the glycaemic control of
# patients differs between medical and surgical wards.
data(inpat_bg)
# Divide patients into strata based on age, gender, duration of monitoring
# episodes, and frequency of daily BG measurements.
inpat_bg$group <- paste(inpat_bg$age_group, inpat_bg$sex, inpat_bg$los_group,
                      inpat_bg$bg_freq_group, sep = "|")
# Fit an RO-logit model with mean BG reading as the outcome and ward as the
# exposure:
```

```
obj <- rologit(yvar = "bg_mean", evar = "ward", svar = "group",
              dat = inpat_bg, initial.res.par = c(2, 2))
summary(obj)
```

---

rologit.coxph	<i>Fit RO-logit model using Cox-PH</i>
---------------	--

---

### Description

Fit RO-logit model using Cox-PH

### Usage

```
rologit.coxph(design.mat, y, svar = NULL, method = "efron")
```

### Arguments

design.mat	The design matrix without intercept term.
y	vector of numeric. The outcomes.
svar	vector of numeric. The strata variable.
method	string. Use Efron ("efron") or Breslow ("breslow") method for handling ties in the outcome. The default is "efron". See <a href="#">coxph</a> for details.

### Value

Returns the model fitted using coxph.

---

summary.rologit	<i>Summarise RO-Logit Model</i>
-----------------	---------------------------------

---

### Description

Prints the estimated coefficients of an RO-Logit model.

### Usage

```
## S3 method for class 'rologit'
summary(object, ...)
```

### Arguments

object	Model object fitted using <a href="#">rologit</a> .
...	Additional arguments affecting the summary produced.

# Index

\* **datasets**

    inpat\_bg, 2

coxph, 5, 6

hresid, 2

inpat\_bg, 2

loglikhresid, 3

optim, 2

qqplot.EVT1, 4

rologit, 4, 6

rologit.coxph, 6

summary.rologit, 6